



N = Number of poles  
 Dim.L=Nx3.5+0.35  
 Dim.P=(N-1)x3.5

Poles	Dim.	Dim.L	Dim.P
2-6p		±0.25	±0.20
7-12p		±0.30	±0.25
13-16p		±0.35	±0.30

SIGN	DATE	DESCRIPTION	APPROVER
△	04/05`12	Operating temperature is changed from -45°C to +130°C to -45°C to +65°C	Guoxue
△	04/05`12	The PART NO is changed	Guoxue
△	04/05`12	The Material is changed	Guoxue

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Materials

- △ Itemⓐ Terminal body:High temp. polyamide (UL94V-0)
- Itemⓑ Terminal screw: Steel Zinc plating "+/-" slot type
- Itemⓒ Wire guard :Stainless steel
- Itemⓓ Terminal :Brass(CuZn) Tin Plated
- Itemⓔ Terminal Cover: High temp. polyamide (UL94V-0)

Electrical UL

- Voltage rating: 150VAC
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 16-26
- Stranded wire(AWG): 16-26
- Torque(Lb-In): 2.0
- Screw: M2.0
- Wire strip length: 5-6mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -45°C to +65°C
- Soldering temperature: 280°C/10 Sec
- Safety Approval:
- Critical dimension:▽
- Part No:

△ EC xx 10 x 0 Bxxx G

- Solid block
  - 02 2 POLES
  - 03 3 POLES
  - ... ..
  - 16 16 POLES
- COLOR  
 0 Black (RAL9005)
- B000 "ⓐ" Logo  
 B00A "ANY" Logo  
 ... ..  
 Any special item by customer request, please contact sales department
- RoHS compliant (lead<4%)  
 In copper Alloy

<b>ANYTEK</b>				<b>CUSTOMER COPY</b>					
								<small>ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD</small>	
TITLE		EC 3.5 Series "+/-"Screw ( With cover & tape reel )							
PART NO.		ECxx10x0BxxxG			DWG NO.		8EC0005		
APPROVED		CHECKED		DESIGNED		DRAWN		CUST NO.	
		Guoxue 2012.07.28		Guoxue 2012.07.28				Tolerance	
								UNIT: mm SCALE: NONE SHEET: 01/01 REV.: B	
								X. ±0.5 X.X ±0.3 X.XX ±0.1 X° ±1°	