



N = Number of poles  
 Dim L = N x 5.0 + 2.8  
 Dim B = (N - 1) x 5.0  
 Dim C = (N - 1) x 5.0 + 5.4  
 Dim D = (N - 1) x 5.0 + 5.4  
 Dim E = (N - 1) x 5.0

Poles	Dim L	Dim B	Dim C	Dim D	Dim E
2x2-2x6p	±0.15	±0.15	+0.05 -0.05	+0.05 -0.05	±0.15
2x7-2x12p	±0.25	±0.25	+0.10 -0.05	+0.10 -0.05	±0.25
2x13-2x18p	±0.35	±0.35	+0.20 -0.05	+0.20 -0.05	±0.35
2x19-2x24p	±0.40	±0.40	+0.25 -0.10	+0.25 -0.10	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	04/16`12	Operating temperature is changed from -40°C to +130°C to -45°C to +120°C	Chen Bo
△	04/16`12	The Material is changed	Chen Bo
△	04/16`12	Add is cULus	Chen Bo
△	04/16`12	The Dimension C & D & E are added	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material:
- Item a Terminal(housing): High temp. polyamide (UL94V-0)
  - Item b Terminal(cover): High temp. polyamide (UL94V-0)
  - Item c Male contact pin of short: Copper Tin plated
  - Item d Male contact pin of long: Copper Tin plated

- Electrical: cULus
- Voltage rating: 300V
  - Current rating: 12A
  - Withstanding Voltage: 1.6KV
  - Operating temperature: -45°C to +120°C
  - Soldering temperature: 280°C/10 Sec
  - Safety Approval: cULus
  - Critical dimension: ∇

KE xx 7 3 x 1 xxxx G

No. OF POLES  
 04: 2x2 POLES  
 06: 2x3 POLES  
 :  
 48: 2x24 POLES

COLOR  
 0: BLACK

RoHS compliant (lead<4%)  
 In copper Alloy

0000: "@" Logo (Standard)  
 000A: "ANYTEK" Mark

Any special item by customer request.  
 please contact sales department.

**ANYTEK**

**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE				KE 5.0mm With latch holder Series 2x2P-2x24P (90°-Right-angle) THR type			
PART NO.		KExx73x1xxxxG		DWG NO.		8KE0113	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
		Chen Bo 04/16`12	Chen Bo 04/16`12			X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°	
SHEET: 01/01				UNIT: mm		SCALE: NONE	
				REV.: C			