



SECTION P-P

Poles	Dim L	Dim B	Dim C
2x2P-2x6P	±0.15	±0.15	±0.15
2x7P-2x12P	±0.25	±0.25	±0.25
2x13P-2x18P	±0.35	±0.35	±0.35
2x19P-2x24P	±0.40	±0.40	±0.40

N = Number of poles
 Dim L=Nx5.0
 Dim B=(N-1)x5.0
 Dim C=(N-1)x5.0

SIGN	DATE	DESCRIPTION	APPROVER
△	04/16'12	Operating temperature is changed from -40°C to +130°C to -45°C to +120°C	Chen Bo
△	04/16'12	The Material is changed	Chen Bo
△	04/16'12	Add is cULus	Chen Bo
△	04/16'12	The dimension Dim C is added	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material:
- Item a Terminal(housing): High temp. polyamide (UL94V-0)
 - Item b Terminal(cover): High temp. polyamide (UL94V-0)
 - Item c Male contact pin of short: Copper Tin plated
 - Item d Male contact pin of long: Copper Tin plated
- Electrical: cULus
- Voltage rating: 300V
 - Current rating: 12A
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -45°C to +120°C
 - Soldering temperature: 280°C/10 Sec
 - Safety Approval: us
 - Critical dimension:

KE xx 7 4 x 1 xxxx G

- No. OF POLES
- 04: 2x2 POLES
 - 06: 2x3 POLES
 - ...
 - 48: 2x24 POLES
- COLOR
- 0: BLACK
- RoHS compliant (lead<4%) In copper Alloy
- 0000: "@ " Logo (Standard)
 000A: "ANYTEK" Mark
- Any special item by customer request. please contact sales department.

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		KE 5.0mm Open Series 2x2P-2x24P (90°-Right angle) THR type					
PART NO.		KExx74x1xxxxG			DWG NO.		8KE0115
APPROVED		CHECKED		DESIGNED		DRAWN	
		Chen Bo 04/16'12		Chen Bo 04/16'12		CUST NO.	
						Tolerance	
				UNIT: mm		X. ±0.50	
				SCALE: NONE		X.X ±0.30	
				SHEET: 01/01		X.XX ±0.10	
				REV.: C		X° ±1°	