


SIGN	DATE	DESCRIPTION	APPROVER
△	3/6'07	增加溝槽尺寸規格	Marvin
△	4/7'09	Voltage,wirerange,torque,operating temperature safety approval are changed	Jody
△	4/7'09	Name changed	Jody

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

### Material

- Item ① Terminal body(metal housing): Steel stamped clamp
- Item ② Terminal screw: Steel Zinc plating "+/-" slot type
- Item ③ Wire guard: Stainless steel
- Item ④ Insulator (housing): Thermoplastic (UL94V-0)

### Electrical cULus

- △ ● Voltage rating: 300VAC
- Current rating: 57A
- Wire range:
- △ ● Solid wire(AWG): 6-22
- △ ● Stranded wire(AWG): 6-22
- △ ● Torque: 13 Lb-In
- Screw: M4
- Wire strip length: 8-9mm
- △ ● Withstanding Voltage: 1.6KV
- △ ● Operating temperature: -40°C to +115°C
- △ ● Safety Approval: 

POLES	DIM A	DIM B	TOL
2P	23.0	12.5	+0.40 -0.40
3P	35.5	25.0	
4P	48.0	37.5	
5P	60.5	50.0	
6P	73.0	62.5	

$$A = (N-1) \times 12.5 + 10.5$$

$$B = (N-1) \times 12.5$$

N=NUMBER OF POLES


EN xx 04 x 0 xxxx G

- |     |         |   |        |  |          |                 |
|-----|---------|---|--------|--|----------|-----------------|
| 02  | 2 Poles | 0 | Black  | 000 0  | @ logo   | G: Pb<40,000ppm |
| 03  | 3 Poles | 4 | Yellow | 000 A  | ANY logo |                 |
| ... | ...     | 5 | Green  | Any special item by customer request, please contact sales department. |          |                 |
| 06  | 6 Poles | 8 | Grey   |  |          |                 |

# ANYTEK

## CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		EN-12.5 Series (2~6P) △			
PART NO.		ENxx04x00000G		DWG NO.	8EN0001
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
		JODY 2009.4.7	JODY 2009.4.7		X. ±0.50
					X.X ±0.30
					X.XX ±0.10
SHEET: 01/01				UNIT: mm	X° ±1°
				SCALE: NONE	
				REV.: D	

