



SIGN	DATE	DESCRIPTION	APPROVER
△	04/19'10	Part NO.is changed	Aaron

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

**Material**

- Item① Clamp : Brass , Ni plated
- Item② Terminal screw: Steel Zinc plating "-" slot type
- Item③ Wire guard solder pin : Brass ,Tin plated
- Item④ Terminal housing : Thermoplastic (UL94V-0)

**Electrical**

- Voltage rating: 300VAC
- Current rating: 20A
- Wire range:
- Solid wire(AWG): 12-22
- Stranded wire(AWG): 12-22
- Torque(Lb-In): 4.3
- Screw: M3
- Wire strip length: 7-8mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety Approval : US

△ EB xx 01 x 3 xxxx G

			RoHS
			Pb<40,000ppm
No. of poles end stackable design	0 Black (RAL9005)	0000:"@Logo (Standard)	
04 2x2 CONTACTS	2 Red (RAL3001/D)	000A:"ANYTEK"Logo	
06 2x3 CONTACTS	3 Orange(RAL2011/P)	Any special item by customer request, please contact sales department.	
... ..	4 Yellow(RAL1018/A)		
... ..	5 Green(RAL6018/T)		
48 2x24 CONTACTS	6 Blue (RAL5015/A)		
	8 Grey(RAL7035/D)		

Poles	2x2	2x3	2x4	2x5	2x6	2x7	2x8	2x9	2x10	2x11	2x12	2x13
Dim L	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00	65.00
Dim B	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00
TOL	±0.20						±0.30					
Poles	2x14	2x15	2x16	2x17	2x18	2x19	2x20	2x21	2x22	2x23	2x24	
Dim L	70.00	75.00	80.00	85.00	90.00	95.00	100.0	105.0	110.0	115.0	120.0	
Dim B	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.0	105.0	110.0	115.0	
TOL	±0.30						±0.40					

## ANYTEK

### CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		EB 5.0mm Series Solder pin in line ( W/o cover )	
PART NO.	EBxx01x3xxxxG △	DWG NO.	8EB0401
APPROVED	CHECKED	DESIGNED	DRAWN
		Aaron 2010.04.19	Kind 2008.12.04
SHEET: 01/01		Tolerance	
		UNIT: mm	X. ±0.50
		SCALE: NONE	X.X ±0.30
		REV.: C	X.XX ±0.10
			X° ±1°