



DIMENSION

Dim A	N/3x5.0
Dim B	(N/3-1)x5.0

N=Number of contacts

Poles	Dim A	Dim B
3x2pole~3x6pole	±0.15	±0.15
3x7pole~3x12pole	±0.25	±0.25
3x13pole~3x18pole	±0.35	±0.35
3x19pole~3x24pole	±0.40	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	09/01'10	Current rating is changed from 20A to 15A	Aaron
△	09/01'10	Add cULus	Aaron

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

**Material**

- Item ① Terminal screw: Steel Zinc plating "-" slot type
- Item ② Clamp: Brass, Ni plating
- Item ③ Wire guard solder pin: Brass, Tin plated
- Item ④ Terminal housing: Thermoplastic (UL94V-0)

**Electrical**

- Voltage rating: 300VAC
- △ ● Current rating: 15A
- Wire range:
  - Solid wire(AWG): 12-28
  - Stranded wire(AWG): 12-28
- Torque(Lb-In): 4.3
- Screw: M3
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec
- △ ● Safety Approval: us

**PART NO.**

YH xx 01 x 1 xxxx G

			RoHS
			Pb<40,000ppm
No. of poles	0	Black (RAL9005)	0000 Standard @ Logo
06 3x2P Contacts	2	Red (RAL3001/D)	000A Standard ANY Logo
09 3x3P Contacts	3	Orange(RAL2011/P)	Any special item by
— — — — —	4	Yellow(RAL1018/A)	customer request,
72 3x24P Contacts	5	Green(RAL6018/T)	please contact sales
	6	Blue (RAL5015/A)	department.
	8	Grey(RAL7035/D)	

<b>ANYTEK</b>		<b>CUSTOMER COPY</b>	
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD			
TITLE	YH 5.0mm Series 3x2P~3x24P ( W/O Cover )		
PART NO.	YHxx01x1xxxxG	DWG NO.	8YH0101
APPROVED	CHECKED	DESIGNED	DRAWN
		Aaron 2010.09.01	Aaron 2010.05.11
SHEET: 01/01		UNIT: mm	Tolerance
		SCALE: NONE	X. ±0.50
		REV.: C	X.X ±0.30
			X.XX ±0.10
			X° ±1°