



SIGN	DATE	DESCRIPTION	APPROVER
△	02/01'07	Soldering temperature changed from 245° to 250°	Tason
△	02/01'07	Part NO is Changed	Tason
△	04/26'07	The test hole is Changed	Aaron
△	11/11'09	Add IEC standard	Aaron
△	11/11'09	Wire guard solder pin is changed from Brass to Copper	Aaron
△	07/15'11	The clamp is changed	Runner
△	07/08'13	update the drawing	Guoxue

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material:
- Item 1 Terminal housing :Thermoplastic (UL 94V-0)
 - Item 2 Clamp : Steel Stamping , Zinc plated
 - Item 3 Wire guard solder pin : Copper , Tin plated
 - Item 4 Terminal screw: Zinc plating"-slot type

- △ Electrical cULus IEC
- Voltage rating: 600V 1000V
- Current rating: 125A 125A
- Wire range: 35mm²
- Solid wire(AWG): 2-20
- Stranded wire(AWG): 2-20
- Torque(Lb-In): 36.5
- Screw: M5
- Wire strip length: 12-15mm
- Withstanding Voltage: 2.2KV 8KV
- Operating temperature: -40° C to +115° C
- △△ Soldering temperature: 260° C±5° C/5 Sec
- Safety Approval: cULus
- Critical dimension: ▽

△△ EI xx C 1 x 30 xxx G

POLES
02 02 POLES
03 03 POLES
.....
10 10 POLES

COLOR
0 Black
2 Red
3 Orange
4 Yellow
5 Green (RAL6018/T)
6 Blue (RAL5015/A)
8 Grey (RAL7035/D)
9 White
C Green(RAL 6018/U)

RoHS compliant (lead<4%)
In copper Alloy

000:"@ "Logo (Standard)
00A:"ANYTEK"Logo
Any special item by customer request, please contact sales department.

Dimension

Poles	02	03	04	05	06	07	08	09	10
Dim L	30.00	45.00	60.00	75.00	90.00	105.00	120.00	135.00	150.00
Dim B	15.00	30.00	45.00	60.00	75.00	90.00	105.00	120.00	135.00
TOL	±0.30		±0.50		±0.80				

ANYTEK

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

CUSTOMER COPY

TITLE		EI 15.0 Series (Double-handed)		
PART NO.	ElxxC1x30xxxG		DWG NO.	8EI0005
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.
		Guoxue 2013.07.08	Guoxue 2013.07.08	
				Tolerance X. ±0.50 X.X ±0.30 X.XX ±0.10 X* ±1*
SHEET: 01/01				UNIT: mm SCALE: NONE REV.: F