



Dimension L&B&C

DIM B	(N-1)×15.0
DIM C	(N-1)×15.0+34.0
DIM L	(N-1)×15.0+45.0

N=Number of poles

Poles	L&B Tolerance
1P-2P	±0.30
2P-4P	±0.50
5P-10P	±0.80

SIGN	DATE	DESCRIPTION	APPROVER
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item 1 Terminal housing :Thermoplastic (UL 94V-0)
  - Item 2 Clamp : Steel Stamping , Zinc plated
  - Item 3 Wire guard solder pin :Copper , Tin plated
  - Item 4 Terminal screw: Zinc plating"-slot type
- Electrical
- Voltage rating: 600V
  - Current rating: 127A
  - Wire range:
  - Solid wire(AWG): 1-20
  - Stranded wire(AWG): 1-20
  - Torque(Lb-In): 36.5
  - Screw: M6
  - Wire strip length: 19-20mm
  - Withstanding Voltage: 2.2KV
  - Operating temperature: -40° C to +115° C
  - Soldering temperature: 260° C±5° C/5 Sec
  - Safety Approval:
  - Critical dimension:

**K9 xx C1 x 31 xxx G**

POLES	COLOR	000:"@"Logo (Standard)	G RoHS compliant (lead<4% In copper Alloy)
01 01 POLES	0 BLACK	00A:"ANYTEK"Logo	
02 02 POLES	5 Green	Any special item by	
03 03 POLES	(RAL6018/T)	customer request,	
.....	6 Blue	please contact sales	
10 10 POLES	8 Grey	department.	
	(RAL7035/D)		
	C Green		
	(RAL6018/U)		

**ANYTEK**

**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	K9 15.0 Series With flange ( Double-handed )				DWG NO.	8K90006	
PART NO.	K9xxC1x31xxxG			CUST NO.			
APPROVED	CHECKED	DESIGNED	DRAWN			Tolerance	
		Guoxue 2013.03.06	Guoxue 2013.03.06			UNIT: mm	X. ±0.50
						SCALE: NONE	X.X ±0.30
						SHEET: 01/01	X.XX ±0.10
						REV.: A1	X* ±1*