



SIGN	DATE	DESCRIPTION	APPROVER
△		THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!	

- Material:
- Item 1 Terminal housing :Thermoplastic (UL 94V-0)
 - Item 2 Clamp : Steel Stamping , Zinc plated
 - Item 3 Wire guard solder pin : Copper , Tin plated
 - Item 4 Terminal screw: Zinc plating"-slot type
- Electrical
- Voltage rating: 600V
 - Current rating: 127A
 - Wire range:
 - Solid wire(AWG): 1-20
 - Stranded wire(AWG): 1-20
 - Torque(Lb-In): 36.5
 - Screw: M6
 - Wire strip length: 19-20mm
 - Withstanding Voltage: 2.2KV
 - Operating temperature: -40° C to +115° C
 - Soldering temperature: 260° C±5° C/5 Sec
 - Safety Approval:
 - Critical dimension:

K9 xx C 1 x 3 0 xxx G

- 01 1 POLES
- 02 2 POLES
- 03 3 POLES
-
- 10 10 POLES

- COLOR
- 0 BLACK
 - 5 Green (RAL6018/T)
 - 6 Blue
 - 8 Grey (RAL7035/D)
 - C Green (RAL6018/U)

000:"@Logo (Standard)
00A:"ANYTEK"Logo
Any special item by customer request, please contact sales department.

G RoHS compliant (lead<4%)
In copper Alloy

Dimension L&B

DIM B	(N-1)×15.0
DIM L	(N-1)×15.0+16

N=Number of poles

Poles	L&B Tolerance
1P-2P	±0.30
3P-4P	±0.50
5P-10P	±0.80

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	K9 15.0 Series without flange (Double-handed)				
PART NO.	K9XXC1X30xxxG		DWG NO.	8K90005	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
		Guoxue 2013.03.06	Guoxue 2013.03.06		X. ±0.50 X.X ±0.30 X.XX ±0.10 X* ±1*
				SHEET: 01/01	UNIT: mm SCALE: NONE REV.: A1