



Dimension L&B&C

DIM B	(N-1)×15.0
DIM C	(N-1)×15.0+34.0
DIM L	(N-1)×15.0+45.0

N=Number of poles

Poles	L&B Tolerance
1P-2P	±0.30
2P-4P	±0.50
5P-10P	±0.80

SIGN	DATE	DESCRIPTION	APPROVER
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item 1 Terminal housing :Thermoplastic (UL 94V-0)
 - Item 2 Clamp : Steel Stamping , Zinc plated
 - Item 3 Wire guard solder pin :Copper , Tin plated
 - Item 4 Terminal screw :Zinc plating"-slot type
- Electrical
- Voltage rating: 600V
 - Current rating: 127A
 - Wire range:
 - Solid wire(AWG): 1-20
 - Stranded wire(AWG): 1-20
 - Torque(Lb-In): 36.5
 - Screw: M6
 - Wire strip length: 19-20mm
 - Withstanding Voltage: 2.2KV
 - Operating temperature: -40° C to +115° C
 - Soldering temperature: 260° C±5° C/5 Sec
 - Safety Approval:
 - Critical dimension:

K9 xx C1 x 21 xxx G

POLES	COLOR	000:"@"Logo (Standard)	G RoHS compliant (lead<4% In copper Alloy)
01 01 POLES	0 BLACK	00A:"ANYTEK"Logo	
02 02 POLES	5 Green (RAL6018/T)	Any special item by customer request,	
03 03 POLES	6 Blue	please contact sales department.	
.....	8 Grey (RAL7035/D)		
10 10 POLES	C Green (RAL6018/U)		

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	K9 15.0 Series With flange (Single-handed)												
PART NO.	K9xxC1x21xxxG		DWG NO.	8K90008									
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance								
		Guoxue 2013.03.06	Guoxue 2013.03.06		<table border="1"> <tr> <td>UNIT: mm</td> <td>X. ±0.50</td> </tr> <tr> <td>SCALE: NONE</td> <td>X.X ±0.30</td> </tr> <tr> <td></td> <td>X.XX ±0.10</td> </tr> <tr> <td></td> <td>X* ±1*</td> </tr> </table>	UNIT: mm	X. ±0.50	SCALE: NONE	X.X ±0.30		X.XX ±0.10		X* ±1*
UNIT: mm	X. ±0.50												
SCALE: NONE	X.X ±0.30												
	X.XX ±0.10												
	X* ±1*												
				SHEET: 01/01	REV.: A1								