

SIGN	DATE	DESCRIPTION	APPROVER
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Technical Data:

Material:

- Pin : Brass,machined, CuZn38Pb2
- Plating : Tin plated:2um/80u"nickel,5um/200u"tin
Gold plated:2um/80u"nickel,Full gold
- Insulator body(housing) : Polyamide(Glass filled)(UL94V-0)
Electrical

- Current rating : 3 Amps/contact max.
- Insulation resistance : >1000MΩ at V=100V
- Operating : 60 Veff


Mechanical:

- Operating temperature: Gold plated:-55°C to +125°C
(continuous) Tin plated:-40°C to +105°C
- Soldering temperture : +260°C,10s max.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		SL series PGA 132P 13.70mmL				
PART NO.	SLE280120000G			DWG NO.	8SL0003-132	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
		Seamus 2008.06.28	Aaron 2008.06.27		UNIT: mm	X. ±0.50
					SCALE: NONE	X.X ±0.30
				SHEET: 01/01	REV.: B	X.XX ±0.10
						X* ±1°