



SECTION P-P

| SIGN | DATE | DESCRIPTION | APPROVER |
|------|----------|-------------------------------|----------|
| △ | 06/28'13 | Add the dimensional label | Jacky |
| △ | 06/28'13 | Add the terminal lever colour | Jacky |
| △ | 06/28'13 | Add the colour code | Jacky |
| △ | 06/28'13 | Change the drawing number | Jacky |
| △ | 06/28'13 | Add the view | Jacky |

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

- Material:
- Item ① Terminal(lever): Thermoplastic (UL94V-0)Orange△
 - Item ② Terminal(up body): Thermoplastic (UL94V-0)
 - Item ③ Wire guard: Stainless steel
 - Item ④ Male contact pin: Phbz.Tin plated
 - Item ⑤ Flange screw NUT: Brass M 2.5
 - Item ⑥ Terminal(down body): Thermoplastic (UL94V-0)
- Electrical: cULus
- Voltage rating: 300 V
 - Current rating: 4 A
 - Wire range:
 - Solid wire(AWG): 16-28
 - Stranded wire(AWG): 16-28
 - Wire strip length: 9-10mm
 - Withstanding Voltage: 1.6 KV
 - Operating temperature: -40°C to +115°C
 - Safety Approval: cULus
 - Critical dimension: ▽

H5 xx 3 0 x 2 xxxx G

No. OF POLES ————

02: 2 POLES

⋮

24: 24 POLES

COLOR ————

0: BLACK

5: GREEN (RAL 6018/T)

6: BLUE

8: GREY (RAL 7035/D)

△C: GREEN (RAL 6018/U)

RoHS compliant (lead<4%) In copper Alloy

0000: "@ " Logo (Standard)

000A: "ANYTEK" Mark

Any special item by customer request. please contact sales department.

| DIM | | TOL | | | |
|------|----------------|-------|--------|---------|---------|
| | | 2P-6P | 7P-12P | 13P-18P | 19P-24P |
| DimA | N×3.81+0.8 | ±0.10 | ±0.15 | ±0.20 | ±0.30 |
| DimB | (N-1)×3.81 | ±0.10 | ±0.15 | ±0.20 | ±0.30 |
| DimC | (N-1)×3.81+9.0 | ±0.15 | ±0.20 | ±0.30 | ±0.40 |
| DimD | N×3.81+10.4 | ±0.15 | ±0.20 | ±0.30 | ±0.40 |

| | | | | | |
|---|--|----------------------|------------|--------------|------------|
| ANYTEK | | CUSTOMER COPY | | | |
| ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD | | | | | |
| TITLE | H5 3.81mm Flange with screw NUT Series | | | | |
| PART NO. | H5xx30x2xxxxG | DWG NO. | 8H50202 △ | | |
| APPROVED | CHECKED | DESIGNED | DRAWN | CUST NO. | Tolerance |
| | | Jacky | Jacky | | X. ±0.50 |
| | | 2013.06.28 | 2013.06.28 | | X.X ±0.30 |
| | | | | | X.XX ±0.10 |
| | | | | | X° ±1° |
| | | | | SHEET: 01/01 | REV.: C |