



Dimension

DIM A	N×5.08
DIM B	(N-1)×5.08
△ DIM C	(N-1)×5.08+10.16
△ DIM D	N×5.08+10.6
△ DIM E	(N-1)×5.08+5.48

N=Number of poles

POLES	TOL
2p-6p	±0.15
7p-12p	±0.20
13p-16p	±0.30
17p-24p	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	06/28'13	Add the dimensional label	Jacky
△	06/28'13	Add the terminal lever colour	Jacky
△	06/28'13	Add the colour code	Jacky
△	06/28'13	Change the drawing number	Jacky
△	06/28'13	Add the view	Jacky
△	06/28'13	Change the dimension from 5.20 to 5.08	Jacky

*THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!*

Material

- Item a Terminal body:Thermoplastic ( UL94V-0 )
- Item b Terminal body:Thermoplastic ( UL94V-0 )
- Item c Terminal lever:Thermoplastic ( UL94V-0 )Orange△
- Item d Wire guard:Stainless Steel
- Item e Male contacta pin:PhBz ( CuSn ) Tin plated
- Item f With flange Nut; Brass M2.5

Electrical

- Voltage rating: 300V
- Current rating: 10A
- Solid wire(AWG): 12-26
- Stranded wire(AWG): 12-26
- Wire strip length: 9-10mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: cULus
- Critical dimension: ▽

H5 xx 50 x 2 xxxx G

- 02 2 CONTACTS
- 03 3 CONTACTS
- ... ..
- 24 24 CONTACTS

0000 Standard @ Logo  
 000A Standard ANY Logo  
 Any special item by customer request, please contact sales department.  
 RoHS compliant (lead<4%)  
 In copper Alloy

- 0: BLACK
- 5: GREEN (RAL 6018/T)
- 6: BLUE
- 8: GREY (RAL 7035/D)
- △C: GREEN (RAL 6018/U)

**ANYTEK**

**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		H5 5.08 Series ( 2P-24P ) ( With flange Nut )				
PART NO.		H5xx50x2xxxxG		DWG NO.		8H50403△
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
		Jacky 2013.06.28	Jacky 2013.06.28			X. ±0.50
				SHEET: 01/01		X.X ±0.30
				REV.: C		X.XX ±0.10
						X* ±1*