



PCB Layout

N=Number of poles
Dim.A= NX9.5+2.5
Dim.B= (N-1)X9.5

POLE	2-6	7-12	13-18
Dim.A	+/-0.20	+/-0.25	+/-0.30
Dim.B	+/-0.10	+/-0.15	+/-0.20

SIGN	DATE	DESCRIPTION	APPROVER
△	2008.2.25	Operating Temp. changed from -40°C+105°C to -40 °C+115°C	kind
△	2008.6.3	SCREW TORQUE VALUE changed from 10 kgf.cm to 8 kgf.cm	kind
△	2008.6.3	WIRE RANGE changed from 22 - 12AWG to 22 - 10AWG	kind
△	2008.6.3	RATED CURRENT changed 20 A to 30 A	kind
△	2008.6.3	The material changed from PVC to PC	kind
△	2008.6.3	APPROVAL:cULus	kind
△	10/27'12	Change the screw plating specification	Jacky
△	10/27'12	Add the dimensional label	Jacky

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

MATERIALS ELECTRICAL

△ RATED VOLTAGE & CURRENT: 300 V, 30 A

WITHSTAND VOLTAGE: AC 2000 V/Min

INSULATION RESISTANCE: 1000 MΩ OR MORE AT DC 500 V

△ OPERATING TEMPERATURE RANG: -40 °C ~ +115 °C

△ SCREW TORQUE VALUE: 8 kgf.cm

△ WIRE RANGE: 22 - 10AWG

1) MOLDED PARTS: Thermoplastic, UL 94 V-0 BLACK

2) TERMINAL: BRASS, 0.8t, Tin PLATED

△ 3) TERMINAL SCREWS: STEEL, M3.5

△ 4) COVER MATERIAL: PC

5) LOCATED PIN : BRASS, 0.8t, Tin PLATED

△ APPROVAL: Critical dimension: ▽

YK 50A xx 2 x x 00G

NO. OF POLES

02: 2 POLES

03: 3 POLES

04: 4 POLES

...

18: 18 POLES

MARK

0: "@" MARK

1: "ANY" MARK

TERMINAL & SCREW PLATED

0: TERMINAL & SCREW: G/F

△ 1: TERMINAL: G/F, SCREW: Zinc

2: TERMINAL: Sn, SCREW: G/F

△ 3: TERMINAL: Sn, SCREW: Zinc

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE		YK50A with cover Series					
PART NO.		YK50Axx2xx00G		DWG NO.		8YK0001-50A	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Jacky	Jacky			X. ±0.50
			2012.10.27	2012.10.27			X.X ±0.30
							X.XX ±0.10
							X° ±1°
				SHEET: 01/01		REV.: D	