



N = Number of poles  
 Dim A = N x 8.25 + 2.0  
 Dim B = (N - 1) x 8.25

Poles	Tol.	Dim A & B
2-5p		±0.20
6-10p		±0.25
11-16p		±0.35
17-24p		±0.40
25-30p		±0.50

SIGN	DATE	DESCRIPTION	APPROVER
△	20/10'06	added cULus approval	Steady
△	03/17'09	Add stipulation	Seamus
△	03/17'09	Dimension is changed	Seamus
△	06/04'11	Critical dimension is changed.	Tason
△	06/04'11	The Wire Range is changed from 20-12AWG to 22-12AWG	Tason
△	06/04'11	The tolerance table is changed.	Tason
△	11/27'12	Change the screw plating specification	Jacky
△	12/07'13	Change the withstand voltage and current	Jacky

*THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!*

MATERIALS ELECTRICAL  
 RATED VOLTAGE & CURRENT: cULus / CQC △  
 WITHSTAND VOLTAGE: 300 V, 20 A/300 V, 32A △  
 INSULATION RESISTANCE: AC 2500 V/Min △  
 OPERATING TEMPERATURE RANG: 1000 MΩ OR MORE AT DC 500 V  
 SCREW TORQUE VALUE: -40 °C ~ +115 °C  
 WIRE RANGE: 8.8 Lb-In.  
 22 - 12 AWG △  
 1) MOLDED PARTS: POLYIMIDE 66, UL 94 V-0 BLACK  
 2) TERMINAL: BRASS, 0.8t, Tin PLATED  
 3) TERMINAL SCREWS: STEEL, M3

- △ Critical dimension: ▽
- △ APPROVAL: cULus CQC △

**YK 335 xx 0 x x 00G** G:RoHS compliant (lead<4%) in copper alloy

NO. OF POLES  
 02: 2 POLES  
 03: 3 POLES  
 04: 4 POLES  
 ...  
 30: 30 POLES

MARK  
 0: "@" MARK  
 1: "ANY" MARK

△ 0: TERMINAL & SCREW: G/F  
 △ 1: TERMINAL: G/F, SCREW: Zinc  
 △ 2: TERMINAL: Sn, SCREW: G/F  
 △ 3: TERMINAL: Sn, SCREW: Zinc

ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD							
TITLE	YK-335 Series			DWG NO.	8YK0001-335		
PART NO.	YK335xx0xx00G			DWG NO.	8YK0001-335		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance		
		Jacky 2013.12.07	Jacky 2013.12.07		X. ±0.50		
					X.X ±0.30		
					X.XX ±0.10		
					X° ±1°		
				SHEET: 01/01	UNIT: mm		
					SCALE: NONE		
					REV.: F		