



N=number of poles
 Dim.L= (N-1)×16.0+52.0
 Dim.A= (N-1)×16.0+32.0
 Dim.B= (N-1)×16.0
 Dim.C= N×16.0+1.0

POLE	Dim.C	Dim.B	Dim.A	Dim.L
2P~6P	±0.40	±0.50	±0.60	±0.70
7P~10P	±0.50	±0.60	±0.70	±0.80

SIGN	DATE	DESCRIPTION	APPROVER
△	07/06'10	Dimension is changed from φ6.2mm to φ6.3mm.	Aaron
△	11/10'10	Current is changed from 75A to 65A	Aaron
△	11/10'10	Wire range is changed from 10-4 AWG to 10-6 AWG	Aaron
△	11/10'10	Add is cULus Mark	Aaron
△	12/12'12	Change the screw plating specification	Jacky
△	12/12'12	Change the dimension from φ6.3mm to φ6.6mm	Jacky

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

MATERIALS ELECTRICAL

RATED VOLTAGE & CURRENT: 600 V, 65A △
 WITHSTAND VOLTAGE: AC 3000 V/Min
 INSULATION RESISTANCE: 1000 MΩ OR MORE AT DC 500 V
 OPERATING TEMPERATURE RANG: -40 °C ~ +115°C
 SCREW TORQUE VALUE: 26 Lb-In.
 WIRE RANGE: 10 - 6 AWG △
 1) BODY: THERMOPLASTICS, UL94-V0 BLACK
 2) TERMINAL: BRASS, 1.6t, Tin PLATED
 △ 3) TERMINAL SCREWS WITH WASHER: STEEL, M6.0
 4) TERMINAL NUT: STEEL Ni PLATED M6.0

APPROVAL: cULus △

PART NO.:

Critical dimension: ▽

YK 901xx3xx00G
 RoHS compliant (lead<4%) In copper Alloy
 MARK
 0: "@" MARK
 1: "ANY" MARK
 TERMINAL & SCREW PLATED
 0: TERMINAL & SCREW: G/F
 △ 1: TERMINAL: G/F, SCREW: Zinc
 2: TERMINAL: Sn, SCREW: G/F
 △ 3: TERMINAL: Sn, SCREW: Zinc

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		YK901 With flange & W/o cover Series				
PART NO.		YK901xx3xx00G		DWG NO.	8YK0003-901	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.	
			Jacky 2012.12.12	Jacky 2012.12.12		
					Tolerance	
					UNIT: mm	X. ±0.50
		SHEET: 01/01			SCALE: NONE	X.X ±0.30
		REV.: D			X.XX ±0.10	X° ±1°