



N=NUMBER OF POLES

Dim L	(N-1)×5.0+6.0
Dim B	(N-1)×5.0

	TOL				
	1--4P	5--9P	10--14P	15--19P	20--24P
Dim L	±0.15	±0.20	±0.30	±0.40	±0.50
Dim B	±0.15	±0.20	±0.30	±0.40	±0.50

SIGN	DATE	DESCRIPTION	APPROVER
△	2/26'07	The Soldering temperature from 245° to 250°	Aaron
△	7/17'09	Oprating Tem.changed to -40°C ~ 115°C	Kind
△	7/17'09	Current rating changed from 7A to 6A	Kind
△	05/23'11	Current rating is changed from 6A to 8A	Steven

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item 1 Insulating body Thermoplastic (UL94V-0)
- Item 2 Insulating cover Thermoplastic (UL94V-0)
- Item 3 Insulating lever Thermoplastic (UL94V-0)
- Item 4 Contact pin Brass, Tin plated
- Item 5 Spring clamp Stainless steel

Electrical cULus

- Voltage rating:300V
- Current rating:8A
- Wire range:
 - Solid wire(AWG):16-26
 - Stranded wire(AWG):16-26
 - Wire strip length:6-7mm
- Withstanding Voltage:1.6KV
- △ ● Operating temperature:-40°C to +115°C
- △ ● Soldering temperature:250°C±10°C/5 Sec
- Safety Approval:
- Critical dimension:

PART NO.

HX xx 00 x 0 xxxx G

- | | | |
|---------------|--------------------|------------------------|
| Poles | 0 Black | 0000 Standard @ Logo |
| 01 1Contacts | 2 Red | 000A Standard ANY Logo |
| 02 2Contacts | 3 Orange | Any special item by |
| | 5 Green(RAL6018/T) | customer request, |
| 24 24Contacts | 8 Grey(RAL7004/P) | please contact sales |
| | 9 White | department. |
| | C Multiple colors | |
- RoHS
Pb<40,000ppm

ANYTEK		CUSTOMER COPY	
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD			
TITLE	HX 5.0 Series Vertical (90° Wire inlet)		
PART NO.	HXxx00x0xxxxG	DWG NO.	8HX0001
APPROVED	CHECKED	DESIGNED	DRAWN
		STEVEN 2011.05.23	STEVEN 2011.05.23
SHEET: 01/01		Tolerance	
UNIT: mm		X. ±0.50	
SCALE: NONE		X.X ±0.30	
REV.: G		X.XX ±0.10	
		X° ±1°	