


SIGN	DATE	DESCRIPTION	APPROVER
△	01/27'07	The soldering temperature from 245° to 250°	Aaron
△	12/13'10	The operating temperature from -30°C to +105°C to -40°C to +115°C	Runner
△	12/13'10	The color is changed	Runner

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item ① Solder Pin(Contact pin) : Brass ,Tin plated
- Item ② Spring clamp : Stainless steel
- Item ③ Terminal cover: Thermoplastic (UL94V-0)
- Item ④ Terminal housing: Thermoplastic (UL94V-0)



Electrical cULus

- Voltage rating:150V
- Current rating:4A
- Wire range:
- Solid wire(AWG):22-28
- Stranded wire(AWG):22-28
- Wire strip length:6-7mm
- Withstanding Voltage:1.3KV
- △ ● Operating temperature:-40°C to +115°C
- △ ● Soldering temperature:250°C±10°C/5 Sec
- Safety approval : 



PART NO.

HE xx 50 x 1 xxxx G

		RoHS
		G: Pb<40,000ppm
Poles		0000 Standard @ Logo
02 2Contacts	0 Black(RAL9005)	000A Standard ANY Logo
03 3Contacts	3 Orange(RAL2011/P)△	Any special item by
...	5 Green(RAL6018/T)	customer request,
12 12Contacts	6 Blue(RAL5015/A)	please contact sales
	8 Grey (RAL7004/P)	department.



N=Number of poles



P.C.B LAYOUT

Dimension

DIM L	N×2.54+1.5
DIM P	(N-1)×2.54


N=Number of poles

POLES	DIM L	DIM P
2p-8p	±0.15	±0.15
9p-12p	±0.25	±0.20

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		HE 2.54 series Without lever			
PART NO.		HExx50x1xxxxG		DWG NO.	8HE0102
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Runner	Aaron		
		2010.12.13	2007.01.27		
					Tolerance
					X. ±0.50
				UNIT: mm	X.X ±0.30
				SCALE: NONE	X.XX ±0.10
				SHEET: 01/01	X° ±1°
				REV.: D	