



N=NUMBER OF POLES  $\Delta$

DIM		TOL		
		1P--6P	7P--12P	13P--16P
Dim P	(N-1)×7.5	±0.15	±0.25	±0.35
Dim L	N×7.5+1.8	±0.15	±0.25	±0.35

SIGN	DATE	DESCRIPTION	APPROVER
$\Delta$	09/15'11	The color is changed from RAL7035/D to RAL7004/P	Runner
$\Delta$	09/15'11	The dimension is changed from 2.1 to 2.2	Runner
$\Delta$	09/15'11	The Material is changed	Runner
$\Delta$	09/15'11	The tolerance is changed	Runner
$\Delta$	09/25'13	change the dimension from 18.6&2.6 to 19.2&3.2	Da cheng
$\Delta$	09/25'13	change the electrical specification	Da cheng

**THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!**

Material:

- Item  $\Delta$  Terminal body: Thermoplastic (UL94V-0)
- Item  $\textcircled{B}$  Terminal side body: Thermoplastic (UL94V-0)
- Item  $\textcircled{C}$  Terminal cover: Thermoplastic (UL94V-0)
- $\Delta$  ● Item  $\textcircled{D}$  Contact pin : Copper, Tin Plated.
- Item  $\textcircled{E}$  Spring clamp : Stainless steel

$\Delta$  Electrical:

- cULus
- Voltage rating: 300 V
- Current rating(Sol): 30 A
- Current rating(Str): 35 A
- Solid wire(AWG): 10-24
- Stranded wire(AWG): 8-24
- Wire strip length: 15-16 mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +120°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval:
- Critical dimension:  $\nabla$

NK xx A 0 x 0 xxxx G

RoHS compliant (lead<4%)  
In copper Alloy  
0000: "@ " Logo (Standard)  
000A: "ANYTEK" Mark  
Any special item by customer request. please contact sales department.

- End Stackable  
01: 1 POLES  
02: 2 POLES  
16: 16 POLES

- $\Delta$  Body Color
- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- $\Delta$  8 Grey(RAL7004/P)
- 9 White(RAL1102)
- C Multiple colors

# ANYTEK

## CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	NK 7.5mm Series Vertical (Double tail A type)(平行脚)			
PART NO.	NKxxA0x0xxxxG	DWG NO.	8NK0001	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.
		Da cheng 2013.09.25	Da cheng 2013.09.25	
SHEET: 01/01				Tolerance
				X. ±0.50
				X.X ±0.30
				X.XX ±0.10
				X° ±1°