

SIGN	DATE	DESCRIPTION	APPROVER
△	12/03'13	Update the drawing	Jacky
△	11/18'14	change the product description ,change the structure	Chenhao
△	04/15'15	Add the safety certification icon	Chenhao

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!


Material

- Item ① Terminal body: PA66 (UL94V-0)
- Item ② Terminal : PhBz,Tin plated.
- Item ③ Terminal cover : PA66 (UL94V-0)

Electrical

cULus

- Voltage rating: 150V
- Current rating: 7A
- Wire range: Solid wire(AWG): 18-22
- Wire strip length: 5-6mm
- Withstanding Voltage: 1.3KV
- Operating temperature: -40°C to +115°C

△ ● Safety approval : 







△ ● Staying power between the body and the cover: 2.5kgf.cm



Critical dimension: ▽

PART No.:

△ NS 01 00 x 0 xxxx G

- △ 0: Black
 - 2: Red
 - 3: Orange
 - 4: Yellow
 - 5: Green(RAL6018/T)
 - 6: Blue (RAL5015/A)
 - 8: Grey(RAL7004/P)
 - 9: White
 - C: Green (RAL 6018/U)
- G:RoHS compliant (lead<4%) In copper Alloy
- 0000: "@ " Logo (Standard)
- 000A: "ANYTEK" Mark with hole



ANYTEK				CUSTOMER COPY			
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD.							
TITLE	NSS.75 series 1P (solid block with hole) △						
PART NO.	NS 0100 x 0 xxxx G △			DWG NO.	8NS0004		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance		
		Chenhao 2015/4/15	Chenhao 2015/4/15		UNIT: mm	X.	±0.50
					SCALE: NONE	X.X	±0.30
				SHEET: 01/01	REV.: E	X.XX	±0.10
						X°	±1°