



Poles	02	03	04	05	06	07	08	09	10	11	12	
Dim L	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00	
Dim B	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	
TOL	±0.15					±0.25					±0.30	

SIGN	DATE	DESCRIPTION	APPROVER
△	2009.08.08	The Solid wire, Operating temperature and Stranded wire are changed	Jacke
△	2009.08.08	Add UL standard	Jacke
△	2009.08.08	Add the tolerance table	Jacke
△	2010.02.07	The workmanship is changed.	Jacke
△	2010.03.29	The design is changed	Jacke
△	2010.04.16	The dimension is changed	Jacke

*THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!*

**Material**

- Item a Clamp: Brass(CuZn) Ni plated
- Item b Terminal screw: Steel Zinc plating "--" slot type
- △ ● Item c Female contact: PhBz (CuSn) Tin plated (Plating before stamping)
- Item d Terminal (housing) : Thermoplastic (UL94 V-0)

**Electrical**

- Voltage rating: 300V
- Current rating: 10A
- Wire range:
- △ ● Solid wire(AWG): 12-26
- △ ● Stranded wire(AWG): 12-26
- Torque: 3.5Lb-In
- Screw: M3.0
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- △ ● Operating temperature: -40°C to +115°C
- △ ● Safety Approval: us
- Use with OP  $\phi 1.3$ mm pin, Withdrawal force: 200 - 500gf /pole

**TX xx 01x0 xxxx G**

- |  |   |   |
|--|---|---|
| 02 2 CONTACTS<br>03 3 CONTACTS<br>... ..<br>12 12 CONTACTS | 0 Black (RAL9005)<br>2 Red (RAL3001/D)<br>3 Orange(RAL2011/P)<br>4 Yellow(RAL1018/A)<br>5 Green(RAL6018/T)<br>6 Blue (RAL5015/A)<br>8 Grey(RAL7035/D) | RoHS<br>Pb<40,000ppm<br>000 0 Standard @ Logo<br>000 A Standard ANY Logo<br>Any special item by<br>customer request,<br>please contact sales<br>department. |
|--|---|---|

**ANYTEK**

**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		TX-5.0mm Series "--" Solid Block Type			
PART NO.		TXxx01x0xxxxG		DWG NO. 8TX0001	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Jacke 2010.04.19	Jacke 2010.02.07		
				UNIT: mm SCALE: NONE SHEET: 01/01 REV.: G	
				Tolerance X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°	