



SIGN	DATE	DESCRIPTION	APPROVER
△	02/11'09	The design changed	Jacke
△	02/11'09	The design changed to revoke	Jacke

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item a Terminal housing:Thermoplastic (UL94V-0)
- Item b Terminal cover:Thermoplastic (UL94V-0)
- Item c Terminal screw:Steel Zinc plating "- "type
- Item d Clamp:Brass, Ni plated
- Item e Female contact:PhBz , Tin plated

Electrical

- Voltage rating: 300V
- Current rating: 15A
- Wire range:
- Solid wire(AWG): 12-28
- Stranded wire(AWG): 12-28
- Torque: 4.5Lb-In
- Screw: M3
- Wire strip length: 5-6mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: us

EO xx 01 x 0 xxxx G

- | | | | | | |
|-----|-------------|---|-------------------|------------------------|--------------|
| 02 | 2 CONTACTS | 0 | Black (RAL9005) | 0000 Standard @ Logo | RoHS |
| 03 | 3 CONTACTS | 2 | Red (RAL3001/D) | 000A Standard ANY Logo | Pb<40,000ppm |
| ... | ... | 3 | Orange(RAL2011/P) | Any special item by | |
| 12 | 12 CONTACTS | 4 | Yellow(RAL1018/A) | customer request, | |
| | | 5 | Green(RAL6018/T) | please contact sales | |
| | | 6 | Blue (RAL5015/A) | department. | |
| | | 8 | Grey(RAL7035/D) | | |

Dim L=N×5.0
Dim B=(N-1)×5.0

Poles	02	03	04	05	06	07	08	09	10	11	12
Dim L	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00
Dim B	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00
TOL	±0.10			±0.15				±0.20			

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		EO 5.0 series (A type ϕ 1.90mm)			
PART NO.	EOxx01x0xxxxG			DWG NO.	8E00001
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
		Jacke 2009.02.23	Jacke 2009.02.23		X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
				UNIT: mm SCALE: NONE SHEET: 01/01	REV.: D