



Dim.L = (N-1) x 7.5+5.5
 Dim.B = (N-1) x 7.5
 N= number of poles

poles Dim.	2P-6P	7P-12P	13P-16P
Dim.L	±0.15	±0.25	±0.35
Dim.B	±0.15	±0.25	±0.35

SIGN	DATE	DESCRIPTION	APPROVER
△	12/03'08	Flange screw changed from "-"solt type to "+/-"solt type	Kind
△	12/03'08	Operating temperature changed from -30 115°C to -40-115°C.	Kind
△	2010.03.10	Add the 2p mark	Jacke

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item (a) Clamp: Brass(CuZn) Ni plated
 - Item (b) Terminal screw: Steel Zinc plating "-" slot type
 - Item (c) Female contact: PhBz ,Tin plated
 - Item (d) Terminal Cover: Thermoplastic (UL94V-0)
 - Item (e) Terminal housing: Thermoplastic (UL94V-0)
 - △ ● Item (f) With flange screw: steel M2.5 Zinc plated "+/-" slot type
- Electrical cULus
- Voltage rating: 300VAC
 - Current rating: 20A
 - Wire range:
 - Solid wire(AWG): 12-24
 - Stranded wire(AWG): 12-24
 - Torque: 5Lb-In
 - Screw: M3
 - Wire strip length: 7-8mm
 - Withstanding Voltage: 1.6KV
 - △ ● Operating temperature: -40°C to +115°C
 - Safety Approval:

TJ xx A1x 2 xxxx G

02 2 CONTACTS
 03 3 CONTACTS

 16 16 CONTACTS

0 Black (RAL9005)
 2 Red (RAL3001/D)
 3 Orange(RAL2011/P)
 4 Yellow(RAL1018/A)
 5 Green(RAL6018/T)
 6 Blue (RAL5015/A)
 8 Grey(RAL7035/D)

RoHS
 Pb<40,000ppm
 000 0 Standard @ Logo
 000 A Standard ANY Logo
 Any special item by
 customer request,
 please contact sales
 department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE				TJ-7.5mm Series with flange 2P-16P			
PART NO.		TJxxA1x2xxxxG		DWG NO.		8TJ0802	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
		Jacke 2010.03.10	Jacke 2010.03.10			UNIT: mm	X. ±0.50
						SHEET: 01/01	REVISION: D
						SCALE: NONE	X.XX ±0.10
						REV.: D	X° ±1°