


N = Number of poles
 Dim A = $N \times 5.0 + 0.50$ Δ
 Dim B = $(N-1) \times 5.0$ Δ

	Dim A	Dim B
2-6p	± 0.15	± 0.15
7-12p	± 0.25	± 0.25
13-18p	± 0.30	± 0.30
19-24p	± 0.40	± 0.40



SIGN	DATE	DESCRIPTION	APPROVER
Δ	11.01'05	Standard spec is changed.	Marivn
Δ	8/07'06	Added VDE and TUV standard	梁仁松
Δ	8/07'06	DWG NO. changed from 8TS0204 to 8TS0004	梁仁松
Δ	12/02'08	With flange screw changed from "-" slot type to "+/-" slot type	Jacke
Δ	12/02'08	The temperature changed from -30°C +105°C to -40°C +115°C	Jacke
Δ	12/02'08	Add the tolerance table	Jacke
Δ	2010.03.13	Add the 2p mark	Jacke
Δ	2010.05.28	The design is changed	Chen Bo
Δ	2010.08.16	The design is changed	Chen Bo

Material

- Item a Clamp: Brass(CuZn) Ni plated
- Item b Terminal screw: Steel Zinc plating "-" slot type
- Item c Female contact: PhBz Tin plated
- Item d Terminal (up body): Thermoplastic (UL94V-0)
- Item e Terminal (down body): Thermoplastic (UL94V-0)
- Δ Item f With flange screw: Steel Zinc plating "+/-" slot type M2.5
- $\Delta \Delta$ Electrical cULus/VDE/TUV
 - Voltage rating: 300VAC/300VAC/300VAC
 - Current rating: 15A/17A/15A
 - Wire range: 2.5mm² /0.34-2.5mm²
 - Solid wire(AWG): 12-24
 - Stranded wire(AWG): 12-24
 - Torque: 3.5Lb-In./0.5Nm/0.4Nm
 - Screw: M3
 - Wire strip length: 6-7mm
 - Withstanding Voltage: 1.6KV/2.5KV/2.5KV
 - Δ ● Operating temperature: -40°C to +115°C
 - Safety approval:

TS xx 71 x D xxxx G

- 02 2 CONTACTS
- 03 3 CONTACTS
-
- 24 24 CONTACTS

- Color
- 0 Black (RAL9005)
 - 2 Red (RAL3001/D)
 - 3 Orange(RAL2011/P)
 - 4 Yellow(RAL1018/A)
 - 5 Green(RAL6018/T)
 - 6 Blue (RAL5015/A)
 - 8 Grey(RAL7035/D)

- RoHS
 Pb<40,000ppm
- 0000: "@" Logo
 - 000A: "ANYTEK" Mark
 - 0091: "ANYTEK" Mark
 - Any special item by customer request. please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE				TS-5.0mm Series(W/latching hooks on the back side) With flange			
PART NO.		TSxx71xDxxxxG		DWG NO.		8TS0004 Δ	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
				Chen Bo			X. ± 0.50
				2010.08.16			X.X ± 0.30
							X.XX ± 0.10
							X° $\pm 1^\circ$
SHEET: 01/01				UNIT: mm		SCALE: NONE	
				REV.: I			