



N = Number of poles  
 Dim A = N x 5.08 + 0.5  
 Dim B = (N - 1) x 5.08

	Dim A	Dim B
2-6p	±0.15	±0.15
7-12p	±0.20	±0.20
13-18p	±0.30	±0.30
19-24p	±0.40	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	11.01'05	Standard spec is changed.	Marivn
△	8/07'06	Added VDE and TUV standard	梁仁松
△	12/02'08	With flange screw changed from "-" slot type to "+/-" slot type	Jacke
△	12/02'08	The temperature changed from -30°C, +105°C to -40°C, +115°C	Jacke
△	12/02'08	Add the tolerance table	Jacke
△	2010.03.12	Add the 2p mark	Jacke
△	2010.08.16	The design is changed	Chen Bo

*THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!*

**Material**

- Item ① Clamp: Brass(CuZn), Ni plating
- Item ② Terminal screw: Steel Cr3+ Zinc plating "-" slot type
- Item ③ Female contact: PhBz, Tin plated
- Item ④ Terminal up body: Thermoplastic (UL94V-0)
- Item ⑤ Terminal down body: Thermoplastic (UL94V-0)
- Item ⑥ With flange screw: Steel Zinc plating M2.5 "+/-" slot type

**Electrical cULus/VDE/TUV**

- Voltage rating: 300VAC/300VAC/300VAC
- Current rating: 15A/17A/15A
- Wire range: 2.5mm /0.34-2.5mm<sup>2</sup>
- Solid wire(AWG): 12-24
- Stranded wire(AWG): 12-24
- Torque: 3.5Lb-In./0.5Nm/0.4Nm
- Screw: M3
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV/2.5KV/2.5KV
- Operating temperature: -40°C to +115°C
- Safety approval: cULus VDE TUV

**TS xx 51 x C xxxx G**

02 2 CONTACTS	Color	RoHS
03 3 CONTACTS		Pb<40,000ppm
... ..		
24 24 CONTACTS		

  

0 0000: "@" Logo
2 000A: "ANYTEK" Mark
3 0091: "ANYTEK" Mark
4 Any special item by customer request.
5 please contact sales department.
6
8

<b>ANYTEK</b>				<b>CUSTOMER COPY</b>					
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD									
TITLE		TS-5.08mm Series(W/latching hooks on the wire entry side) with flange				DWG NO.		8TS0103	
PART NO.		TSxx51xCxxxxG				APPROVED		CHECKED	
APPROVED		DESIGNED		DRAWN		CUST NO.		Tolerance	
				Chen Bo				X. ±0.50	
				2010.08.16				X.X ±0.30	
						UNIT: mm		X.XX ±0.10	
						SCALE: NONE		X° ±1°	
						SHEET: 01/01		REV.: H	