



SIGN	DATE	DESCRIPTION	APPROVER
△	12/02'08	Flange screw changed from "-" to "+/-"	Tony
△	2009.10.10	Add UL standard	Jacke
△	2010.02.06	The Wire strip length is changed	Jacke
△	2010.03.23	Add the 2p mark	Jacke

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

**Material**

- Item a Clamp: Steel zinc plated.
- Item b Terminal screw: Brass Zinc plating "-" slot type
- Item c Female contact: PhBz Tin plated
- △ ● Item d With flange screw: Steel zinc plated M2.5 "+/-" slot type
- Item e Terminal (Up body): Thermoplastic (UL94V-0)
- Item f Terminal (Down body): Thermoplastic (UL94V-0)
- Item g Clampage: Steel Zinc plated
- Electrical cULus
- Voltage rating: 300VAC
- Current rating: 20A
- Wire range: 0.34-2.5mm<sup>2</sup>
- Solid wire(AWG): 12-22
- Stranded wire(AWG): 12-22
- Torque: 3.5Lb-In
- Screw: M2.5
- △ ● Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- △ ● Safety approval:

**VM xx A 5 x 3 xxxx G**

- POLES ————
- 02: 02 pole  
 ... ..  
 16: 16 pole
- Color
- 0 Black (RAL9005)
  - 2 Red (RAL3001/D)
  - 3 Orange(RAL2011/P)
  - 4 Yellow(RAL1018/A)
  - 5 Green(RAL6018/T)
  - 6 Blue (RAL5015/A)
  - 8 Grey(RAL7035/D)
- G: Pb<40000ppm
- 0000: "@" Logo (Standard)  
(Steel screw plating Cr<sup>3+</sup>)
  - 000A: "ANYTEK" Mark
  - Any special item by customer request.
  - please contact sales department.

POLE	2	3	4	5	6	7	8	
A	13.00	20.50	28.00	35.50	43.00	50.50	58.00	
B	7.50	15.00	22.50	30.00	37.50	45.00	52.50	
Tol.	±0.10			±0.20				
POLE	9	10	11	12	13	14	15	16
A	65.50	73.00	80.50	88.00	95.50	103.00	110.50	118.00
B	60.00	67.50	75.00	82.50	90.00	97.50	105.00	112.50
Tol.	±0.30			±0.40				

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		VM 7.5 mm W/ Flange Series					
PART NO.		VMxxA5x3xxxxG			DWG NO.		8VM0401
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		 Tolerance X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
			Jacke 2010.03.23	Jacke 2009.10.10	 UNIT: mm SCALE: NONE SHEET: 01/01 REV.: E		