







SIGN	DATE	DESCRIPTION	APPROVER
△	1/26/07	Soldering temperature changed from 245° to 250°	Tony
△	04/08'09	Add TUV standard	Jacke
△	04/08'09	Add the tolerance table	Jacke
△	2009.10.21	The material is changed from Brass to Copper	Jacke
△	2010.12.08	The design is changed	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- △ ● Item ① Male contact pin: Copper Tin plated
 - Item ② Terminal(housing): Thermoplastic (UL94V-0)
- | | | |
|----------------------------|---|---|
| Electrical: | cULus | TUV |
| ● Voltage rating: | 300V | 750V |
| ● Current rating: | 20A | 15A |
| ● Withstanding Voltage: | 1.6 KV | 6KV |
| ● Operating temperature: | -40°C to +115°C | |
| △ ● Soldering temperature: | 250°C±10°C/5 Sec | |
| △ ● Safety Approval: |  |  |



RECOMMENDED PCB LAYOUT

DIMENSION △

A	(N-1)X7.62+5.8
B	(N-1)X7.62

N= NUMBER OF CONCATS

Poles	Tolerance
2P-6P	±0.20
7P-12P	±0.30
13P-16P	±0.40

OQ xx 0 0 x 0 xxxx G

No. OF POLES
02: 2 POLES
:
16: 16 POLES


COLOR
0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)

G: Pb<40000ppm
0000: "@ " Logo (Standard)
000A: "ANYTEK" Mark
Any special item by customer request.
please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		OQ 7.62mm 180° /Open Series 2p-16p			
PART NO.		OQxx00x0xxxxG		DWG NO.	80Q0304
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
			Chen Bo 2010.12.08	 UNIT: mm SCALE: NONE SHEET: 01/01 REV.: G	Tolerance
					X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°