



SIGN	DATE	DESCRIPTION	APPROVER
△	2011.08.24	The dimension are added	Aaron
△	2011.08.24	Dimension is changed from 10.16mm to 10.00mm	Aaron
△	2011.08.24	Dimension is changed from 2.42mm to 2.50mm	Aaron
△	2012.04.16	Add the cutaway view	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item ③ Short male Contact pin: Copper ,Tin plated
- Item ④ Long male Contact pin: Copper ,Tin plated
- Item ⑤ With flange nut: brass M2.5
- Item ⑥ Terminal (housing): Thermoplastic (UL94V-0)

Electrical

- Voltage rating: 300VAC
- Current rating: 10A
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec
- Safety Approval: us
- Critical dimension: ▽

VF xx 72 x 1 xxxx G

- Poles
- 04 2×2Poles
 - 06 2×3Poles
 -
 - 48 2×24Poles

- RoHS compliant (lead<4%) In copper Alloy
- 0000 Standard @ Logo
- 000A Standard ANY Logo
- Any special item by customer request, please contact sales department.
- Color
- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)
- 9 White(RAL1102)
- C Green(RAL6018/U)

N=NUMBER OF CONTACTS

Dimension	TOL					
	2×2P-2×5P	2×6P-2×10P	2×11P-2×15P	2×16P-2×20P	2×21P-2×24P	
Dim L	(N/2+2)×5.0	±0.15	±0.20	±0.25	±0.30	±0.40
Dim B	(N/2-1)×5.0	±0.15	±0.20	±0.25	±0.30	±0.40
Dim C	(N/2-1)×5.0	±0.15	±0.20	±0.25	±0.30	±0.40
Dim D	(N/2-1)×5.0+10.0	±0.15	±0.20	±0.25	±0.30	±0.40

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		VF-5.00 Series 2×2P-2×24P (With flange) Right-angle			
PART NO.		VFxx72x1xxxxG		DWG NO. 8VF0001	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Chen Bo 04/17'12	Chen Bo 04/17'12	Tolerance	
					X. ±0.50
					X.X ±0.30
					X.XX ±0.10
					X° ±1°
				SHEET: 01/01	REV.: D