



DIM		TOL			
		2P-6P	7P-12P	13P-18P	19P-24P
Dim L	(N-1)×5.08+7.08	±0.15	±0.25	±0.30	±0.40
Dim B	(N-1)×5.08	±0.15	±0.25	±0.30	±0.40
Dim C	N×5.08		+0.0 -0.20		+0.0 -0.40
Dim D	(N-1)×5.08	±0.15	±0.25	±0.30	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	04.20'09	The design is changed	Jacke
△	04.20'09	The operating temperature is changed	Jacke
△	2010.01.12	Add cULus standard	Jacke
△	2010.03.31	Add the 2p mark	Jacke
△	2010.04.26	The current rating is changed from 10A to 20A	Jacke
△	2014.09.12	The current rating is changed from 20A to 10A	Evan

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Materials

- Item Ⓐ Terminal body: Thermoplastic (UL94V-0)
- Item Ⓑ Female contact: PhBz Tin plated
- Item Ⓒ Terminal cover: Thermoplastic (UL94V-0)

Electrical cULus

- Voltage rating: 300VAC
- Current rating: 10A
- Withstanding Voltage: 1.6kv
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval: cULus
- Critical dimension: ▽

V7 xx 5 1 x 0 xxxx G

- No. OF POLES
- 02 2 plocs
 - 03 3 plocs
 - ...
 - 24 24 plocs

- Color
- 0 Black (RAL9005)
 - 2 Red (RAL3001/D)
 - 3 Orange (RAL2011/P)
 - 4 Yellow (RAL1018/A)
 - 5 Green (RAL6018/T)
 - 6 Blue (RAL5015/A)
 - 8 Grey (RAL7035/D)
 - 9 White (RAL1102)
 - C Green (RAL6018/U)
- G RoHS compliant (lead<4%)
In copper Alloy
- 0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
- Any special item by customer request, please contact sales department.

ANYTEK

INSPECTION COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		V7 5.08 Series Vertical			
PART NO.		V7xx51x0xxxxG		DWG NO. 8V70301	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Evan 09/12'14	Evan 09/12'14	Tolerance	
				UNIT: mm	
				SCALE: NONE	
SHEET: 01/01				REV.: G	
				X.	±0.5
				X.X	±0.3
				X.XX	±0.1
				X°	±1°