



SECTION P-P

N = Number of poles

Dim.A	$N \times 7.62$
Dim.B	$(N-1) \times 7.62$
Dim.C	$(N+1) \times 7.62$
Dim.D	$(N+2) \times 7.62$

Poles	Tolerance
3P	±0.20
4P	

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item (a) Terminal(housing) : PA66 (UL94V-0)
- Item (b) Terminal(cover) : PA66 (UL94V-0) (ET 7.62)
- Item (c) Terminal screw : Steel Zinc plating " - " slot type (ET 7.62)
- Item (d) Clamp : Brass, Ni plated (ET 7.62)
- Item (e) Female contact : Copper, Tin plated
- Item (f) With flange Nut : Steel Zinc plating M3 (VC 7.62)
- Item (g) Steel : Steel t=1.50mm zinc plated.

Electrical

- Voltage rating: 600VAC
- Current rating: 41A
- Solid wire (AWG): 8-24
- Stranded wire(AWG): 8-24
- Torque: 9.0 Lb-In
- Screw: M3.5
- Wire strip length: 10-11mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval:
- Critical dimension:

KT xx 0 1 x 3 xxxx G

No. OF POLES
03: 3 POLES
04: 4 POLES

G: Pb<40000ppm

0000: "@" Logo (Standard)
000A: "ANYTEK" Mark

COLOR

- 0 Black (RAL9005)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)
- C Green(RAL6018/U)

Any special item by customer request. please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	KT 7.62 Series Flange With Nut (With handle) Only 3P & 4P				DWG NO.	8KT0017	
PART NO.	KTxx01x3xxxxG			CUST NO.			
APPROVED	CHECKED	DESIGNED	DRAWN	UNIT: mm SCALE: NONE SHEET: 01/01 REV.: B			
		Aaron 2011.10.18	Aaron 2011.10.18				
				Tolerance		X.	±0.50
						X.X	±0.30
						X.XX	±0.10
						X°	±1°