



N=NUMBER OF POLES

DIM		TOL			
		2P--5P	6P--8P	9P--12P	13P--16P
Dim A	$(N+2) \times 7.62$	± 0.30	± 0.35	± 0.40	± 0.50
Dim B	$(N+1) \times 7.62$	± 0.30	± 0.35	± 0.40	± 0.50
Dim C	$N \times 7.62$	± 0.30	± 0.35	± 0.40	± 0.50
Dim D	$(N-1) \times 7.62$	± 0.30	± 0.35	± 0.40	± 0.50

SIGN	DATE	DESCRIPTION	APPROVER
	12/11/12	Change the dimensional tolerance	Chen Bo
	09/26/13	add the safety certification icon	Chen Bo
	09/26/13	change the electrical specification	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item Left Cover :Thermoplastic (UL94 - V0)
- Item Middel Body :Thermoplastic (UL94 - V0)
- Item Right Cover :Thermoplastic (UL94 - V0)
- Item Contact pin: Copper Tin plated
- Item Wire guard:Stainless Steel (ET 7.62)
- Item Flange Nut: Steel , Zinc plated M3 (VC 7.62)

Electrical:

cULus

- Voltage rating: 300V
- Current rating: 41A
- Withstanding Voltage:1.6 KV
- Operating temperature:-40°C to +115°C
- Soldering temperature:260°C \pm 5°C/5 Sec
- Safety approval:
- Critical dimension:

K S xx 0 2 x 0 xxxx G

No. OF POLES
02: 2 POLES
16: 16 POLES

COLOR
0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)
9 White(RAL1102)
C Green(RAL6018/U)

G RoHS compliant (lead<4%) In copper Alloy
0000: "@ " Logo (Standard)
000A: "ANYTEK" Mark
Any special item by customer request. please contact sales department.

ANYTEK				CUSTOMER COPY				
								ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD
TITLE		KS 7.62 Series 2P-16P Vertical (With Flange)						
PART NO.		KSxx02x0xxxxG			DWG NO.		8KS0002	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
			Chen Bo	Chen Bo			X. ± 0.50	
			09/26/13	12/11/12			X.X ± 0.30	
					SHEET: 01/01		X.XX ± 0.10	
					REV.: D		X° $\pm 1^\circ$	