



SIGN	DATE	DESCRIPTION	APPROVER
△	03/29`12	Add is cULus	Chen Bo
△	03/29`12	The dimension is changed from 11.40mm to 11.4mm	Chen Bo
△	03/29`12	The dimension D & E are added	Chen Bo
△	03/29`12	The dimension is changed from 1.30mm to 1.3mm	Chen Bo
△	03/29`12	The dimension is changed from 2.60mm to 2.6mm	Chen Bo
△	03/29`12	Flange nut is changed	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item a Terminal(housing): Thermoplastic (UL94V-0)
 - Item b Terminal(cover): Thermoplastic (UL94V-0)
 - Item c Male contact pin of short: Copper Tin plated
 - Item d With flange nut: Brass M2.5
- Electrical:** cULus
- Voltage rating: 300V
 - Current rating: 12A
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - Soldering temperature: 250°C ±10°C/5 Sec
 - Safety Approval: cULus
 - Critical dimension:

KE xx 5 2 x 2 xxxx G

- No. OF POLES
- 04: 2x2 POLES
 - 06: 2x3 POLES
 - 48: 2x24 POLES
- COLOR
- 0 Black (RAL9005)
 - 2 Red (RAL3001/D)
 - 3 Orange(RAL2011/P)
 - 4 Yellow(RAL1018/A)
 - 5 Green(RAL6018/T)
 - 6 Blue (RAL5015/A)
 - 8 Grey(RAL7035/D)
 - 9 White(RAL1102)
 - C Green(RAL6018/U)
- G RoHS compliant (lead<4%) In copper Alloy
- 0000: "@ " Logo (Standard)
000A: "ANYTEK" Mark
- Any special item by customer request. please contact sales department.

N = Number of poles
 Dim L=(N+1)×5.08+4.84
 Dim P=(N-1)×5.08
 Dim C=(N-1)×5.08+5.4
 Dim D=(N-1)×5.08+5.4
 Dim E=(N-1)×5.08

Poles	Dim L	Dim P	Dim C	Dim D	Dim E
2×2-2×6p	±0.15	±0.15	+0.05 -0.05	+0.05 -0.05	±0.15
2×7-2×12p	±0.25	±0.25	+0.10 -0.05	+0.10 -0.05	±0.25
2×13-2×18p	±0.35	±0.35	+0.20 -0.05	+0.20 -0.05	±0.35
2×19-2×24p	±0.40	±0.40	+0.25 -0.10	+0.25 -0.10	±0.40

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		KE 5.08mm With Flange Series ((Vertical) DIP TYPE			
PART NO.	KExx52x2xxxxG	DWG NO.	8KE0210		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
		Chen Bo 03/29`12	Chen Bo 03/29`12		X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
					UNIT: mm
					SCALE: NONE
				SHEET: 01/01	REV.: C